

Model name	Valve type	Overall tap height	Spout exit reach	Spout exit height	base plinth diameter	Max. worktop thickness (mm)	Minimum water pressure (bar)	Tail pipe inlet	Spout flow characteristics
Alto Duo	trigger & single lever	700	175-500	135	50	60	1	3/8" BSP Female	single flow
Alto Professional	trigger & single lever	700	160-500,240	135,240	45	40	1	1/2" BSP Male	single flow
Antlia monobloc	ceramic disc QT	375	230	235	50	60	0.3	1/2" BSP Male	single flow
Arkitekt single lever	single lever ceramic cartridge	342	220	235	50	60	0.5	1/2" BSP Male	single flow
Aron aquifier - stainless steel	3 - way single lever ceramic	390	215	251	50	40	0.5	1/2" BSP Male	single flow
Aspley monobloc	ceramic disc QT	237	225	205	55	35	0.2	15mm y	dual flow
Atlas 4 Part with pull out spray rinse	trigger & ceramic disc QT	280	225	170	50,50,50,50	15	0.4	1/2" BSP Male	single flow
Atlas Aquifier	ceramic disc QT	395	225	255	60	60	0.3	15mm y	(C&F / H) dual flow
Atlas monobloc	ceramic disc QT	395	225	255	60	60	0.2	15mm y	dual flow
Atlas single lever	single lever ceramic cartridge	395	220	260	60	55	0.5	15mm y	single flow
Avior monobloc	ceramic disc QT	440	210	235	58	20	0.4	1/2" BSP Male	single flow
Avior monobloc with pull out	ceramic disc QT	440	210-600	235	58	20	0.5	1/2" BSP Male	single flow
Axell handspray - stainless steel	trigger	131	0-1200	108	55	40	0.5	1/2" BSP Male	single flow
Berkeley Bridge	ceramic disc QT	320	180	225	50	80	0.1	1/2" BSP Male	single flow
Berkeley monobloc	Q-Tech (QT compression)	335	190	212	53	25	0.3	15mm y	dual flow
Corvus single lever	joystick ceramic cartridge	355	170	205	48	60	0.5	1/2" BSP Male	single flow
Diagon single lever	single lever ceramic cartridge	310	220	210	42 x 58	75	0.5	1/2" BSP Male	single flow
Diagon single lever - stainless steel	single lever ceramic cartridge	323	194	182	64 x 45	40	0.5	1/2" BSP Male	single flow
Draco with pull out spray rinse	single lever ceramic cartridge	165	204 - 850	110	55	40	0.5	1/2" BSP Male	single flow
Electra single lever	joystick ceramic cartridge	325	190	182	48	60	0.5	1/2" BSP Male	single flow
Eltham monobloc	ceramic disc QT	270	215	240	50	20	0.2	15mm y	dual flow
Gosford Aquifier	ceramic disc QT	390	230	245	50	65	0.3	15mm y	(C&F / H) dual flow
Gosford monobloc	ceramic disc QT	390	230	245	50	60	0.2	15mm y	dual flow
Gresham	ceramic disc QT	285	190	209	55	40	0.3	15mm y	single flow
Hand pull out spray rinse	trigger	180	0-1200	160	50	40	1	1/2" BSP Female	single flow
Hydrus single lever	single lever ceramic cartridge	250	190	185	50	50	0.5	1/2" BSP Male	single flow
Ignus single lever - stainless steel	single lever ceramic cartridge	283	186	209	50	40	0.5	1/2" BSP Male	single flow
Indus single lever	single lever ceramic cartridge	286	205	235	45	45	0.5	1/2" BSP Male	single flow
Ludlow Bridge	ceramic disc QT	330	185	235	50	80	0.1	1/2" BSP Male	single flow
Ludlow monobloc	ceramic disc QT	355	190	225	49	15	0.2	15mm y	dual flow
Lupus monobloc	Q-Tech (QT compression)	365	185	235	50	50	0.3	15mm y	dual flow
Melford Bridge	ceramic disc QT	260	220	190	45	30	0.1	1/2" BSP Male	single flow
Melford monobloc	ceramic disc QT	245	225	175	58	60	0.2	1/2" BSP Male	single flow
Milo	ceramic disc QT	290	220	213	54	50	0.3	1/2" BSP Male	single flow
Pavo 3 Part	ceramic disc QT	245	170	165	45,45,45	45	0.5	1/2" BSP Male	single flow
Pictor single lever	single lever ceramic cartridge	352	160	215	45	80	1	3/8" BSP Female	single flow
Pixie	ceramic disc QT	304	160	172	45	40	0.3	1/2" BSP Male	single flow
Propus single lever - stainless steel	single lever ceramic cartridge	295	235	195	50	65	0.5	1/2" BSP Male	single flow
Ratio Pro	single lever ceramic cartridge	465	220-290	180	45	40	0.5	1/2" BSP Male	single flow
Ratio single lever	single lever ceramic cartridge	435	220	215	45	45	0.5	1/2" BSP Male	single flow
Ratio single lever with pull out	single lever ceramic cartridge	435	220-600	215	45	45	0.5	1/2" BSP Male	single flow
Sirius single lever	single lever ceramic cartridge	195	229	170	55	35	0.3	1/2" BSP Male	single flow
Somerley monobloc	Q-Tech (QT compression)	275	225	208	55	20	0.2	15mm y	dual flow
Tate	ceramic disc QT	288	210	226	56	40	0.3	15mm y	single flow
Tuscan single lever	single lever ceramic cartridge	300	220	215	50	50	0.5	1/2" BSP Male	single flow
Ursa single lever	single lever ceramic cartridge	175	220	150	50	40	0.3	1/2" BSP Male	single flow
Vega monobloc	ceramic disc QT	320	160	235	50	50	0.3	15mm y	dual flow
Vixo - stainless steel	Progressive ceramic disc QT	275	206	250	50	40	0.5	1/2" BSP Male	single flow
Wilton monobloc	ceramic disc QT	340	180	213	49	20	0.2	15mm y	dual flow

All taps require a 35mm y tap hole, product supplied in a branded box with protective packaging and cloth bag  
Specifications are subject to change. All errors and omissions excepted.